



在使用本产品前请仔细阅读本手册，本将其放在设备附近以备将来参阅。

Before use, please read this manual carefully and be placed nearby to the equipment for future reference



CHENG

上海上诚泵阀制造有限公司

SHANGHAISHANGCHENG PUMP AND VALVE MANUFACTURING CO.,LTD

地址(Add): 上海市普陀区中山北路1759号

Shanghai Putuo District No.1759 in
Zhongshan North Road

邮编(Post):200010

电话(Tel):021-68100000

传真(Fax):021-61398677

网址(Http): //www.scpv.cn




CHENG

上诚泵阀 因诚而信
Shangcheng Pump and valve
Being trustworthy because of its sincerity



用户使用手册
User operating brochure



上海上诚泵阀制造有限公司

SHANGHAI SHANGCHENG PUMP AND VALVE MANUFACTURING CO.,LTD



上海上诚泵阀制造有限公司是一家集科研、开发、生产、销售于一体的泵阀企业；公司拥有一支经验丰富、勇于实践、不断创新的高素质开发、科研队伍：其中高级工程师2名，研究、设计技术人员35名，生产技术制造人员68名，现有员工总数达298人；公司拥有国内外先进的电脑微机控制性能水泵测试台，使客户更安全、更有效、更放心地使用上诚产品。公司全面采用ISO9001：

2000《质量管理体系要求》，并有效的实施；自创办以来始终把质量管理作为第一追求目标，发扬拼搏精神，争创一流的精神在泵阀行业中不断发展壮大。公司主要生产经营各类水泵及配套蝶阀；产品畅销全国各地，广泛应用于石油、化工、电力、造纸、食品、制药、给排水工程等，深受各行业用户的一致好评，上诚秉着“以诚为贵，以质取胜”的经营理念，诚心为您提供优质的品牌产品和完美的服务，竭诚欢迎社会各界惠顾合作。



企业简介 BRIEF INTRODUCTION




Shanghai Shangcheng Pump and valve manufacturing Co.,Ltd. is an enterprise of Researching, developing, producing and selling; The company has an experienced team to develop high quality products, 2 senior engineers, 35 designing engineers, 68 technicians, which totally amounts to 298; The company has the domestic advanced automatical system to perform water pump test, which can make the customer to use our products safely, effective and easily.

The ISO9001:2000"quality control system request" always be implemented effectively; since our company is opened, the quality control is always our first pursue goal and we are growing strong in the pump and valve industry.

Our main products are pumps and matched valves, which are sold to the strongly all over of China, it can be widely applied to petroleum, chemical industry, electric power, papermaking, food, drugs manufacturing and so on, "honesty oriented, quality comes first" is our management idea, which sincerely provides the high quality brand product and the consummation service for you.

▶ IHF 型氟塑料衬里离心泵

IHF Fluoroplastics Liner Centrifugal Pump




▶ 简介及特点 Brief Introduction and Features

- IHF型氟塑料衬里离心泵是我公司致力于聚全氟乙丙烯（简称F46）衬里离心泵自行开发研究的化工泵，产品以其合理的结构，优良的密封性能，备受化工、冶金、石油、离子膜和军事工程等行业单位青睐，九十年代我们又根据国内外有关资料经消化、吸收，博采取长、精心设计，开发成功新一代耐强腐蚀IHF系列离心泵，它几乎可以抵抗任何种类的酸、碱、盐、氧化物和有机溶剂的强烈腐蚀，产品行销全国各省市。
- IHF type fluoroplastics liner centrifugal pump is F46 liner chemical pump which is developed by our selves independently. Because of its proper structure and excellent sealing result, these products are very cared by chemical industry, metallurgy, oil membrane and military engineering etc. In 90s, we successfully developed a new generational higher corrosion proof IHF series centrifugal pump according to domestic and foreign relative information. It almost can resist all kinds of strong corrosion such as chasacid, alkali, salt, oxide and organically solvent etc. The product was sold very well all over the country.
- IHF离心泵按国际标准设计，泵体采用金属外壳内衬聚全氟乙丙烯（F46），泵盖、叶轮和轴套均用金属嵌件外包氟塑料整体烧结压制成型，轴封采用外装式波纹管机械密封，静环选用99.9%（氧化铝陶瓷或氮化硅），动环采用四氟填充材料，其特点是防腐、耐磨、密封性能优越可靠。
- IHF type centrifugal pump is designed according to international standards. The pump body is made by metal housing and FEP (F46) lining, pump cover, impeller and shaft sleeve are made by integrated sintering and pressure moulding of metal insert and fluoroplastic housing, shaft seal is sealed by external waviness mechanical seal, stationary seal ring is made of 99.9% Alumina ceramics or silicon nitride, and rotating seal ring is made of PTFE stuffing materials, with features such as corrosion proof, abrasion proof and excellent and reliable sealing performance.

▶ 主要用途 Main Applications

- 本泵适用于输送任何浓度的硫酸、盐酸、醋酸、氢氟酸、硝酸、王水、强碱、强氧化剂、有机溶剂，还原剂等苛刻条件的强腐蚀性介质，是目前世界上最新耐腐蚀装备之一。它的最大优点是结构先进合理、密封性能严密可靠、拆卸检修方便、工作稳定、噪声低、使用寿命长。
- This pump can be used in transporting harsh and strong erosive medium of any density such as viriol, hydrochloric, organic dissolvent and reducing agent etc. It is one of the most latest erosion proof equipments in the world. Its biggest advanced and logical structure, reliable sealing performance, convenient dismantling and repair, stable operation, low noise and long life.
- 使用温度:-30℃~150℃.
Operating temperature: -30℃~150℃.


► IHF型泵结构图 Structural Drawing of IHF Pumps




► IHF型泵主要零部件表 Main Parts Table of IHF Pumps

序号 No.	1	2	3	4	5	6	7	8	9	10	11	12
名称 Name	泵体 Pump body	叶轮骨架 Impeller Skeleton	叶轮 Impeller	泵体衬里 Pump body Lining	泵盖衬里 Pump Cover Lining	泵盖 Pump Cover	机封压盖 Mechanical Seal Gland	静环 Still ring	动环 Movable ring	泵轴 Pump Shaft	轴承体 Bearing Body	联轴器 Coupling
材料 Material	HT200	45#	聚全氟 乙丙烯 F46	聚全氟 乙丙烯 F46	聚全氟 乙丙烯 F46	HT200	1Cr18Ni9Ti	99.9%氧化 铝陶瓷 99.9% alumin um oxidelam eramics	填充四 氟乙烯 Filled with pife	3Cr13	HT200	HT200

► 型号意义 Designation




▶ IHF型泵性能曲线图 Performance Curve of IHF Pumps



性能参数表 Performance Parameters

Type	转速 r/min	流量Q m³/h	Capacity L/S	Head (m)	效率 η%	Power kW	Neve Sory (NPSH)r (m)	Impeller Diameter (mm)	Weight (kg)
型号	转速	m³/h	L/S	扬程	效率	轴功率 电机功率	必需汽蚀余量	叶轮直径	重量
IHF32-25-125	2900	3.5	0.97	21	40	0.50	2.3	128	80
		5	1.39	20	44	0.62			
		6.5	1.80	18	42	0.76			
IHF32-25-125A	2900	1.75	0.49	5.25	37	0.068	2.3	128	75
		2.5	0.69	5	40	0.085			
		3.25	0.90	4.5	38	0.105			
IHF32-25-125A	2900	3.1	0.86	17.6	38	0.70	2.3	115	75
		4.5	1.25	16	41	0.48			
		5.8	1.61	14.4	40	0.57			
IHF32-25-160	2900	3.5	0.97	33	34	0.93	2.3	162	90
		5	1.39	32	40	1.10			
		6.5	1.80	30	42	1.26			
IHF32-25-160A	2900	1.75	0.49	8.25	30	0.131	2.3	162	75
		2.5	0.69	8	38	0.143			
		3.25	0.90	7.5	40	0.166			
IHF32-25-160A	2900	3.1	0.86	29	30	0.81	2.3	152	80
		4.5	1.25	28	35	0.97			
		5.8	1.61	26	36	1.14			
IHF40-32-125	2900	4.4	1.22	21	40	0.63	2.5	128	90
		6.5	1.80	20	45	0.79			
		8.3	2.31	18	43	0.95			
IHF40-32-125	1450	2.2	0.60	5.25	37	0.085	2.5	128	75
		3.25	0.90	5	41	0.108			
		4.15	1.15	4.5	40	0.127			
IHF40-32-125A	2900	3.9	1.08	17.6	38	0.49	2.5	115	80
		5.6	1.56	16	42	0.58			
		7.4	2.06	14.4	40	0.72			

安装尺寸图 Installation Dimensions Drawing




安装尺寸表 Installation Dimensions

Type	Motor type / Power (KW)	外形及安装尺寸 Outline and Installation Dimensions										
产品型号	电机型号/功率	L	B	S	P	A	W	T	H	h	f	4- Φd
IHF32-25-125	Y802-4/0.75	780	730	470	120	60	320	270	350	220	80	4- Φ19
	Y802-2/1.1	780	730	470	120	60	320	270	350	220	80	4- Φ19
	Y90S-2/1.5	790	730	470	120	60	320	270	350	220	80	4- Φ19
IHF32-25-160	Y802-4/0.75	780	730	470	120	60	320	270	350	220	80	4- Φ19
	Y90S-2/1.5	790	740	530	130	60	350	300	370	230	80	4- Φ19
	Y90L-2/2.2	810	740	530	130	60	350	300	370	230	80	4- Φ19
IHF40-32-125	Y802-4/0.75	780	730	470	120	60	320	270	350	220	80	4- Φ19
	Y90S-2/1.5	790	730	470	120	60	320	270	350	220	80	4- Φ19
	Y90L-2/2.2	820	730	470	120	60	320	270	350	220	80	4- Φ19

性能参数表 Performance Parameters

Type 型号	转速 r/min	流量Q Capacity m³/h L/S		Head (m) 扬程	Efficiency η% 效率	Power kW 轴功率 电机功率		Neve Sory (NPSH)r (m) 必需汽蚀余量	Impeller Diameter (mm) 叶轮直径	Weight (kg) 重量
IHF40-32-160	2900	4.4	1.22	33	34	1.16				
		6.5	1.80	32	40	1.42				
		8.3	2.31	30	39	1.71				
IHF40-32-160A	2900	2.2	0.60	8.25	33	0.14				
		2.5	0.90	8	36	0.15				
		3.25	1.15	7.5	37	0.18				
IHF40-32-160A	2900	3.9	1.08	29	32	0.96				
		5.6	1.56	28	38	1.23				
		7.4	2.06	26	37	1.41				
IHF50-32-125	2900	8.8	1.08	21.5	45	1.15				
		12.5	1.56	20	54	1.26				
		16.3	2.06	17.5	53	1.47				
IHF50-32-125	1450	4.4	1.2	5.37	37	0.17				
		6.25	1.74	5	46	0.18				
		8.15	2.26	4.37	45	0.22				
IHF50-32-125A	2900	8	2.22	17	42	0.88				
		11	3.05	16	52	0.92				
		14.5	4.03	14	51	1.08				
IHF50-32-160	2900	8.8	2.44	33	41	1.93				
		12.5	3.47	32	48	2.27				
		16.3	4.53	30	47	2.84				
IHF50-32-160	1450	4.4	1.2	8.25	31	0.31				
		6.25	1.74	8	41	0.33				
		8.15	2.26	7.5	42	0.39				
IHF50-32-160A	2900	8.2	2.28	29	39	1.16				
		11.7	3.25	28	47	1.88				
		15.2	4.22	26	46	2.34				

安装尺寸图 Installation Dimensions Drawing




安装尺寸表 Installation Dimensions

Type 产品型号	Motor type / Power (KW) 电机型号/功率	外形及安装尺寸 Outline and Installation Dimensions										
		L	B	S	P	A	W	T	H	h	f	4- Φd
IHF40-32-160	Y802-4/0.75	780	740	530	130	60	320	270	350	230	80	4- Φ19
	Y90S-2/1.5	800	740	530	130	60	350	300	370	230	80	4- Φ19
	Y90L-2/2.2	810	740	530	130	60	350	300	370	230	80	4- Φ19
IHF50-32-125	Y802-4/0.75	800	740	530	130	60	350	300	370	230	80	4- Φ19
	Y90S-2/1.5	810	750	530	130	60	350	300	360	220	80	4- Φ19
	Y90L-2/2.2	820	750	530	130	60	350	300	360	220	80	4- Φ19
IHF50-32-160	Y802-4/0.75	820	820	560	130	60	350	300	370	235	80	4- Φ19
	Y100L-2/3	900	800	455	175	60	390	340	480	220	80	4- Φ19
	Y112M-2/4	900	820	560	130	60	350	300	370	235	80	4- Φ19

性能参数表 Performance Parameters

Type	 r/min 转速	 流量Q Capacity		Head (m)	 Efficiency $\eta\%$	 Power kW		Neve Sory (NPSH)r (m)	Impeller Diameter (mm)	Weight (kg)
型号	转速	m ³ /h	L/S	扬程	效率	轴功率	电机功率	必需汽蚀余量	叶轮直径	重量
IHF50-32-200	2900	8.8 12.5 16.3	2.44 3.47 4.53	52 50 48	34 42 41	3.70 4.10 5.20	7.5	3.0	190	150
	1450	4.4 6.25 8.15	1.2 1.74 2.26	13 12.5 12	25 33 36	0.62 0.65 0.74	1.5	3.0	190	100
IHF50-32-200A	2900	8.2 11.7 15.2	2.28 3.25 4.22	45 44 42	31 40 39	3.24 3.50 4.45	5.5	3.0	178	130
	2900	8.8 12.5 16.3	2.44 3.47 4.53	82 80 76	27 35 34	7.30 7.80 10	11	3.0	250	220
IHF50-32-250	2900	8.2 11.7 15.2	2.28 3.25 4.22	71 70 68	25 34 33	4.53 6.56 8.52	7.5	3.0	235	170
	2900	17.5 25 32	4.86 6.94 9.0	21.5 20 17.5	56 64 63	1.83 2.13 2.42	3	3.5	128	100
IHF65-50-125	2900	8.75 12.5 16	2.43 3.47 4.44	5.37 5 4.37	45 57 58	0.28 0.30 0.33	0.75	3.5	128	80
	2900	15.6 22.3 29	4.33 6.19 8.1	17 16 14	53 62 61	1.36 1.57 1.79	2.2	3.5	115	90

安装尺寸图 Installation Dimensions Drawing




安装尺寸表 Installation Dimensions

Type	Motor type / Power (KW)	外形及安装尺寸 Outline and Installation Dimensions										
产品型号	电机型号/功率	L	B	S	P	A	W	T	H	h	f	4-Φd
IHF50-32-200	Y90L-4/1.5	850	800	560	130	60	350	300	370	235	80	4-Φ19
	Y132S1-2/5.5	970	850	560	140	60	390	340	380	260	80	4-Φ19
	Y132S2-2/7.5	980	850	560	140	60	390	340	380	260	80	4-Φ19
IHF50-32-250	Y100L1-4/2.2	1030	920	560	200	80	480	430	520	290	100	4-Φ24
	Y132S2-2/7.5	1180	1170	775	200	80	490	440	520	290	100	4-Φ24
	Y160M1-2/11	1280	1170	775	200	80	490	440	520	290	100	4-Φ24
IHF65-50-125	Y802-4/0.75	800	750	530	130	60	350	300	360	220	80	4-Φ19
	Y90L-2/2.2	850	820	560	130	60	350	300	370	235	80	4-Φ19
	Y100L-2/3	870	770	550	110	60	320	270	360	220	80	4-Φ19

性能参数表 Performance Parameters

Type	 r/min 转速	 流量Q Capacity		Head (m)	 Efficiency η %	 Power kW		Neve Sory (NPSH)r (m)	Impeller Diameter (mm)	Weight (kg)
型号	转速	m³/h	L/S	扬程	效率	轴功率	电机功率	必需汽蚀余量	叶轮直径	重量
IHF65-50-160	2900	17.5 25 32	4.86 6.94 9.0	33 32 27.5	50 59 57	3.15 3.69 4.20	5.5	3.5	160	145
	1450	8.75 12.5 16	2.43 3.47 4.44	8.25 8 6.87	40 53 51	0.49 0.51 0.59	1.1	3.5	160	90
IHF65-50-160A	2900	16.4 23.3 30.4	4.56 6.5 8.44	29 28 24	48 58 56	2.70 3.10 3.54	4	3.5	150	130
IHF65-40-200	2900	17.5 25 32	4.86 6.94 9.0	52 50 45.5	45 54 54	5.50 6.30 7.35	11	3.5	195	225
	1450	8.75 12.5 16	2.43 3.47 4.44	13 12.5 11.4	36 46 47	0.86 0.93 1.05	1.5	3.5	195	100
IHF65-40-200A	2900	16.4 23.3 30.4	4.56 6.5 8.44	46 44 40	43 53 52	4.30 5.00 5.20	7.5	3.5	183	170
IHF65-40-250	2900	17.5 25 32	4.86 6.94 9.0	82 80 76	39 50 52	10.10 10.90 12.74	18.5	3.5	250	240
	1450	8.75 12.5 16	2.43 3.47 4.44	20.5 20 19	32 42 44	1.52 1.62 1.88	3	3.5	250	130
IHF65-40-250A	2900	16.4 23.3 30.4	4.56 6.5 8.44	71 70 68	36 48 50	8.80 9.30 11.25	15	3.5	235	230

安装尺寸图 Installation Dimensions Drawing




安装尺寸表 Installation Dimensions

Type	Motor type / Power (KW)	外形及安装尺寸 Outline and Installation Dimensions										
产品型号	电机型号/功率	L	B	S	P	A	W	T	H	h	f	4- Φd
IHF65-50-160	Y90S-4/1.1	870	820	560	120	60	390	340	400	235	80	4- Φ19
	Y112M-2/4	900	820	560	120	60	350	300	370	235	80	4- Φ19
	Y132S1-2/5.5	960	840	600	120	60	390	340	400	235	80	4- Φ19
IHF65-40-200	Y90L-4/1.5	990	880	560	140	60	390	340	380	260	100	4- Φ19
	Y132S2-2/7.5	1120	850	560	140	60	390	340	380	260	100	4- Φ19
	Y160M1-2/11	1140	980	660	150	60	460	400	440	260	100	4- Φ19
IHF65-40-250	Y100L2-4/3	1030	920	560	200	80	480	430	520	290	100	4- Φ19
	Y160M2-2/15	1180	1170	775	200	80	490	430	520	290	100	4- Φ19
	Y160L-2/18.5	1330	1170	775	200	80	490	430	520	290	100	4- Φ24

性能参数表 Performance Parameters

Type		 流量Q Capacity		Head (m)	 Efficiency $\eta\%$	 Power kW		Neve Sory (NPSH)r (m)	Impeller Diameter (mm)	Weight (kg)
型号	转速	m ³ /h	L/S	扬程	效率	轴功率	电机功率	必需汽蚀余量	叶轮直径	重量
IHF80-65-125	2900	35 50 65	9.72 13.9 18.1	21.5 20 17	64 69 67	3.20 3.95 4.50	5.5	4.0	134	150
	1450	17.5 25 32.5	4.86 6.9 9.0	5.37 5 4.25	54 64 62	0.47 0.53 0.61	1.1	4.0	134	90
IHF80-65-125A	2900	31 45 58	8.6 12.5 16.1	17 16 14	62 68 67	2.30 2.88 3.30	4	4.0	120	130
IHF80-65-160	2900	35 50 65	9.72 13.9 18.1	33 32 27.5	60 68 67	5.24 6.41 7.27	11	4.0	165	220
	1450	17.5 25 32.5	4.86 6.9 9.0	8.25 8 6.88	50 62 61	0.78 0.88 1.00	1.5	4.0	165	100
IHF80-65-160A	2900	31 45 58	8.6 12.5 16.1	29 28 24	58 67 66	4.10 5.12 5.34	7.5	4.0	165	190
IHF80-50-200	2900	35 50 65	9.72 13.9 18.1	52 50 45.5	52 64 65	9.53 10.64 12.39	15	4.0	197	230
	1450	17.5 25 32.5	4.86 6.9 9.0	13 12.5 11.38	51 59 58	1.21 1.44 1.74	3	4.0	197	130
IHF80-50-200A	2900	31 45 58	8.6 12.5 16.1	46 44 40	50 63 62	7.35 8.56 10	11	4.0	185	220

安装尺寸图 Installation Dimensions Drawing




安装尺寸表 Installation Dimensions

Type	Motor type / Power (KW)	外形及安装尺寸 Outline and Installation Dimensions										
产品型号	电机型号/功率	L	B	S	P	A	W	T	H	h	f	4- Φd
IHF80-65-125	Y90S-4/1.1	820	800	560	130	60	350	300	370	235	100	4- Φ24
	Y112M-2/4	900	820	560	130	60	350	300	370	235	100	4- Φ24
	Y132S1-2/5.5	980	840	600	120	60	390	340	400	235	100	4- Φ24
IHF80-65-160	Y90L-4/1.5	840	800	560	130	60	390	340	380	260	100	4- Φ24
	Y132S2-2/7.5	1040	850	560	140	60	390	340	380	260	100	4- Φ24
	Y160M1-2/11	1140	980	660	150	60	460	400	440	260	100	4- Φ24
IHF80-50-200	Y100L2-4/3	940	850	560	140	60	390	340	380	260	100	4- Φ24
	Y160M1-2/11	1000	960	660	150	60	460	400	460	270	100	4- Φ24
	Y160M2-2/15	1020	960	660	150	60	460	400	460	270	100	4- Φ24

性能参数表 Performance Parameters

Type 型号	 转速	流量Q  Capacity		Head (m) 扬程	 效率	Power  KW		Neve Sory (NPSH)r (m) 必需汽蚀余量	Impeller Diameter (mm) 叶轮直径	Weight (kg) 重量
		m ³ /h	L/S			轴功率	电机功率			
IHF80-50-250	2900	35 50 65	9.72 13.9 18.1	82 80 72	40 50 51	19.40 21.80 25	30	4.0	248	400
	1450	17.5 25 32.5	4.86 6.9 9.0	20.5 20 18	40 50 51	2.40 2.70 3.12	4	4.0	248	145
IHF80-50-250A	2900	31 45 58	8.6 12.5 16.1	71.5 70 63	39 50 51	15.40 17.60 19.90	22	4.0	232	310
IHF100-80-125	2900	70 100 130	19.4 27.8 36.1	23 20 14	70 75 65	6.26 7.26 7.63	11	5.0	136	220
	1450	35 50 65	9.7 13.9 18.0	5.75 5 3.5	65 70 64	0.85 0.97 0.98	1.5	4.5	136	100
IHF100-80-125A	2900	62.5 89 116	17.4 24.7 32.2	18 16 11	68 73 65	4.50 5.30 5.74	7.5	5.0	122	200
IHF100-80-160	2900	70 100 130	19.4 27.8 36.1	34 32 24	68 74 65	9.53 11.78 13.03	15	5.0	170	230
	1450	35 50 65	9.7 13.9 18.0	8.5 8 6.5	60 68 67	1.35 1.60 1.69	2.2	4.5	170	110
IHF100-80-160A	2900	65.4 93.5 121	18.2 26 33.6	32 28 21	66 73 65	8.60 9.30 10.6	11	5.0	159	220

安装尺寸图 Installation Dimensions Drawing




安装尺寸表 Installation Dimensions

Type 产品型号	Motor type / Power (KW) 电机型号/功率	外形及安装尺寸 Outline and Installation Dimensions										
		L	B	S	P	A	W	T	H	h	f	4- Φd
IHF80-50-250	Y112M-4/4	1050	920	560	200	80	480	430	510	285	100	4- Φ24
	Y180M-2/22	1330	1170	775	200	80	490	430	510	285	100	4- Φ24
	Y200L1-2/30	1430	1270	850	220	80	550	490	510	285	100	4- Φ24
IHF100-80-125	Y90L-4/1.5	960	800	560	130	80	390	340	380	260	100	4- Φ24
	Y132S2-2/7.5	1040	850	560	140	80	390	340	380	260	100	4- Φ24
	Y160M1-2/11	1140	980	660	150	80	460	400	440	270	100	4- Φ24
IHF100-80-160	Y100L1-4/2.2	940	850	560	140	80	390	340	460	270	100	4- Φ24
	Y160M1-2/11	1120	1090	760	165	80	460	400	480	280	100	4- Φ24
	Y160M2-2/15	1140	1090	760	165	80	460	400	480	280	100	4- Φ24

性能参数表 Performance Parameters

Type	 r/min 转速	 流量Q Capacity		Head (m)	 Efficiency $\eta\%$	 Power kW		Neve Sory (NPSH)r (m)	Impeller Diameter (mm)	Weight (kg)
型号	转速	m ³ /h	L/S	扬程	效率	轴功率	电机功率	必需汽蚀余量	叶轮直径	重量
IHF100-65-200	2900	70 100 130	19.4 27.8 36.1	52 50 42	64 72 71	15.50 18.91 20.94	30	5.0	210	400
	1450	35 50 65	9.7 13.9 18.0	13 12.5 10.5	60 68 63	2.06 2.50 2.95	4	4.5	210	140
IHF100-65-200A	2900	65.4 93.5 121	18.2 26 33.6	46 44 37	63 71 70	13 15.02 17.40	22	5.0	197	310
IHF100-65-250	2900	70 100 130	19.4 27.8 36.1	87 80 68	62 69 68	26.60 31.60 35	45	4.0	255	450
	1450	30 50 60	8.33 13.9 16.7	21.2 20 18.5	58 63 62	3.00 4.30 4.72	5.5	4.5	255	170
IHF100-65-250A	2900	65.4 93.5 121	16.2 26 33.6	76.5 70 59	60 68 67	20.25 26.2 28	37	4.5	238	410


安装尺寸图 Installation Dimensions Drawing



安装尺寸表 Installation Dimensions

Type	Motor type / Power (KW)	外形及安装尺寸 Outline and Installation Dimensions										
产品型号	电机型号/功率	L	B	S	P	A	W	T	H	h	f	4- Φd
IHF100-65-200	Y112M-4/4	1050	920	560	200	80	480	430	525	300	100	4- Φ28
	Y180-2/22	1280	1220	880	190	80	570	500	525	300	100	4- Φ28
	Y200L1-2/30	1380	1220	880	190	80	570	500	525	300	100	4- Φ28
IHF100-65-250	Y132S-4/5.5	1140	950	560	160	80	610	510	550	300	100	4- Φ28
	Y200L2-2/37	1380	1220	880	200	80	630	525	550	300	100	4- Φ28
	Y225L-2/45	1780	1450	1280	200	80	630	560	550	300	100	4- Φ28

进出口法兰示意图 Inlet & Outlet Flange Sketch Map



法兰尺寸表 Flange Dimensions

Type	进口法兰尺寸 Inlet flange dimensions					出口法兰尺寸 Outlet flange dimensions				
型号	c	a	b	e	n-d	k	g	i	j	n-t
IHF32-25-125	32	120	90	16	4-14	25	100	75	16	4-14
IHF32-25-160										
IHF40-32-125	40	130	100	18	4-14	32	120	90	18	4-14
IHF40-32-160										
IHF50-32-125	50	165	125	20	4-18	32	140	100	18	4-18
IHF50-32-160						32	145	110	18	
IHF50-32-200										
IHF50-32-250										
IHF65-50-125	65	185	145	20	4-18	50	165	125	20	4-18
IHF65-50-160						40	150	110	18	
IHF65-40-200										
IHF65-40-250										
IHF80-65-125	80	200	160	20	8-18	65	185	145	20	4-18
IHF80-65-160						50	165	125	20	
IHF80-50-200										
IHF80-50-250										
IHF100-80-125	100	220	180	22	8-18	80	200	160	20	8-18
IHF100-80-160						65	185	145	20	4-18
IHF100-65-200										
IHF100-65-250										